



**Farmer
Traktor**

**Low Cost
Models**

FT

7258R 8258R

9258R 10258R



FARMER FT Low Cost Models

Dedicated for developing countries . Also available with optional cabin.

Model		FT-7258R	FT-8258R	FT-9258R	FT-10258R
Engine	Rated power	52 kW (70 HP)	60 kW (80 HP)	66 kW (90 HP)	74 kW (99 HP)
	Torque [Nm @ rpm]	281 @ 1000	292 @ 1200	374 @ 1200	372 @ 1400
	Engine brand	John Deere	John Deere	John Deere	John Deere
	Engine type	4 cylinders	4 cylinders	4 cylinders, turbocharged	4 cylinders, turbocharged
	Engine displacement	4,52 dm ³	4,52 dm ³	4,52 dm ³	4,52 dm ³
	Cranking assistance	Sparking plug	Sparking plug	Sparking plug	Sparking plug
Air filter	Dry, dust-laden indicator	Dry, dust-laden indicator	Dry, dust-laden indicator	Dry, dust-laden indicator	
Steering system		Hydrostatic power steering	Hydrostatic power steering	Hydrostatic power steering	Hydrostatic power steering
Front drive axle	Brand	CARRARO	CARRARO	CARRARO	CARRARO
	Actuation	Electro - hydraulic	Electro - hydraulic	Electro - hydraulic	Electro - hydraulic
Transmission	Type	Mechanical, synchronized	Mechanical, synchronized	Mechanical, synchronized	Mechanical, synchronized
	Gears	12x12 (option 24x24)	12x12 (option 24x24)	12x12 (option 24x24)	12x12 (option 24x24)
	Reverse	Mechanical	Mechanical	Mechanical	Mechanical
	Brand	CARRARO	CARRARO	CARRARO	CARRARO
Clutch	Dry, double-plate	Dry, double-plate	Dry, double-plate	Dry, double-plate	
Brakes		Hydraulic, disc, oil immersed	Hydraulic, disc, oil immersed	Hydraulic, disc, oil immersed	Hydraulic, disc, oil immersed
	Type	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift
Hydraulic system	Pump oil flow	58 dm ³ /min	58 dm ³ /min	58 dm ³ /min	58 dm ³ /min
	Max. pressure in the system	180 Bar	180 Bar	180 Bar	180 Bar
	External hydraulics	Double ISO couplers	Double ISO couplers	Double ISO couplers	Double ISO couplers
	Lift capacity	2500 kg or 3000 kg (additional cylinder-option)	2500 kg or 3000 kg (additional cylinder-option)	2500 kg or 3000 kg (additional cylinder-option)	2500 kg or 3000 kg (additional cylinder-option)
Power Take-off (PTO)	Speed range	540/1000 rpm	540/1000 rpm	540/1000 rpm	540/1000 rpm
	Type	Independent and ground speed PTO	Independent and ground speed PTO	Independent and ground speed PTO	Independent and ground speed PTO
Weights	Complete weight	3125 kg	3125 kg	3125 kg	3125 kg
	Weight distribution (front/rear)	1495 / 1630 kg	1495 / 1630 kg	1495 / 1630 kg	1495 / 1630 kg
Tires	Front	11,2x24	11,2x24	12,4x24	12,4x24
	Rear	16,9x30	16,9x30	18,4x30	18,4x30
Options	Lower hitch/Pick-up hitch	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
	Front Three Point Linkage	Yes	Yes	Yes	Yes
	Rear ballast	2x50 kg or 4x50 kg	2x50 kg or 4x50 kg	2x50 kg or 4x50 kg	2x50 kg or 4x50 kg
	Front ballast	6 x 45 kg	6 x 45 kg	6 x 45 kg	6 x 45 kg
	Pneumatic seat	Yes	Yes	Yes	Yes
	Pneumatic system	1- or 2 circuit	1- or 2 circuit	1- or 2 circuit	1- or 2 circuit
	Additional cylinder	Yes	Yes	Yes	Yes
	Fuel tank capacity	125 dm ³	125 dm ³	125 dm ³	125 dm ³

FT2

8248R

9248R



2WD

&

4WD

FARMER FT2 Low Cost Models

Dedicated for developing countries . Also available with optional cabin.

Model		FT2-8248R	FT2-9248R
Engine	Rated power	59,6 kW (81 HP)	70 kW (95 HP)
	Torque [Nm @ rpm]	290 @ 1400	411 @ 1400
	Engine brand	MMZ	MMZ
	Engine type	4 cylinders	4 cylinders, turbocharged
	Engine displacement	4,75 dm ³	4,75 dm ³
	Cranking assistance	Sparking plug	Sparking plug
	Air filter	Dry, dust-laden indicator	Dry, dust-laden indicator
Steering system		Hydrostatic power steering	Hydrostatic power steering
Front drive axle	Brand	CARRARO	CARRARO
	Actuation	Electro - hydraulic	Electro - hydraulic
Transmission	Type	Mechanical, synchronized	Mechanical, synchronized
	Gears	12x12 (option 24x24)	12x12 (option 24x24)
	Reverse	Mechanical	Mechanical
	Brand	CARRARO	CARRARO
Brakes	Clutch	Dry, double-plate	Dry, double-plate
		Hydraulic, disc, oil immersed	Hydraulic, disc, oil immersed
Hydraulic system	Type	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift
	Pump oil flow	47 or 55 dm ³ /min	47 or 55 dm ³ /min
	Max. pressure in the system	180 Bar	180 Bar
	External hydraulics	Double ISO couplers	Double ISO couplers
	Lift capacity	2500 kg or 3000 kg (additional cylinder-option)	2500 kg or 3000 kg (additional cylinder-option)
Power Take-off (PTO)	Speed range	540/1000 rpm	540/1000 rpm
	Type	Independent and ground speed PTO	Independent and ground speed PTO
Weights	Complete weight	3340 kg	3340 kg
	Weight distribution (front/rear)	1610 / 1830 kg	1610 / 1830 kg
Tires	Front	11,2x24	12,4x24
	Rear	16,9x30	18,4x30
Options	Lower hitch/Pick-up hitch	Yes / Yes	Yes / Yes
	Front Three Point Linkage	Yes	Yes
	Rear ballast	2x50 kg or 4x50 kg	2x50 kg or 4x50 kg
	Front ballast	6 x 45 kg	6 x 45 kg
	Pneumatic seat	Yes	Yes
	Pneumatic system	1- or 2 circuit	1- or 2 circuit
	Additional cylinder	Yes	Yes
	Fuel tank capacity	125 dm ³	125 dm ³

FT4

7148R 7248R

8148R 8248R



2WD & 4WD

FARMER FT4 Low Cost Models

Dedicated for developing countries . Also available with optional cabin.

Model		FT4-7148R	FT4-7248R	FT4-8148R	FT4-8248R
Engine	Rated power	52,9 kW (72 HP)	52,9 kW (72 HP)	59,6 kW (81 HP)	59,6 kW (81 HP)
	Torque [Nm @ rpm]	267 @ 1400	267 @ 1400	290 @ 1400	290 @ 1400
	Engine brand	MMZ	MMZ	MMZ	MMZ
	Engine type	4 cylinders	4 cylinders	4 cylinders	4 cylinders
	Engine displacement	4,75 dm ³	4,75 dm ³	4,75 dm ³	4,75 dm ³
	Cranking assistance	Sparking plug	Sparking plug	Sparking plug	Sparking plug
Air filter	Dry, dust-laden indicator	Dry, dust-laden indicator	Dry, dust-laden indicator	Dry, dust-laden indicator	
Steering system		Hydrostatic power steering	Hydrostatic power steering	Hydrostatic power steering	Hydrostatic power steering
Front drive axle	Brand	CARRARO	CARRARO	CARRARO	CARRARO
	Actuation	Mechanically	Mechanically	Mechanically	Mechanically
Transmission	Type	Mechanical, synchronized	Mechanical, synchronized	Mechanical, synchronized	Mechanical, synchronized
	Gears	8x8 (option 12x12)	8x8 (option 12x12)	8x8 (option 12x12)	8x8 (option 12x12)
	Reverse	Mechanical	Mechanical	Mechanical	Mechanical
	Brand	CARRARO	CARRARO	CARRARO	CARRARO
Clutch	Brand	CARRARO	CARRARO	CARRARO	CARRARO
	Clutch	Dry, double-plate	Dry, double-plate	Dry, double-plate	Dry, double-plate
Brakes		Hydraulic, disc, oil immersed	Hydraulic, disc, oil immersed	Hydraulic, disc, oil immersed	Hydraulic, disc, oil immersed
Hydraulic system	Type	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift	Universal with forcible regulation, mixing control, steering of lifting speed, blocking of lift
	Pump oil flow	47 or 55 dm ³ /min	47 or 55 dm ³ /min	47 or 55 dm ³ /min	47 or 55 dm ³ /min
	Max. pressure in the system	180 Bar	180 Bar	180 Bar	180 Bar
	External hydraulics	Double ISO couplers	Double ISO couplers	Double ISO couplers	Double ISO couplers
	Lift capacity	2000 kg	2000 kg	2000 kg	2000 kg
Power Take-off (PTO)	Speed range	540/540E rpm	540/540E rpm	540/540E rpm	540/540E rpm
	Type	Independent and ground speed PTO	Independent and ground speed PTO	Independent and ground speed PTO	Independent and ground speed PTO
Weights	Complete weight	2945 kg	3105 kg	2945 kg	3105 kg
	Weight distribution (front/rear)	1395 / 1550 kg	1510 / 1595 kg	1395 / 1550 kg	1510 / 1595 kg
Tires	Front	7,5-16	11,2x24	7,5-16	11,2x24
	Rear	16,9x30	16,9x30	16,9x30	16,9x30
Options	Lower hitch/Pick-up hitch	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
	Front Three Point Linkage	Yes	Yes	Yes	Yes
	Rear ballast	2x32 kg + max 6x24 kg	2x32 kg + max 6x24 kg	2x32 kg + max 6x24 kg	2x32 kg + max 6x24 kg
	Front ballast	6x45 kg	6x45 kg	6x45 kg	6x45 kg
	Pneumatic seat	Yes	Yes	Yes	Yes
	Pneumatic system	1- circuit	1- circuit	1- circuit	1- circuit
	Additional cylinder	No	No	No	No
	Fuel tank capacity	100 dm ³	100 dm ³	100 dm ³	100 dm ³



**Farmer
Traktor**

Farmer Traktor Sp. z o.o. has made every effort to provide accurate information in this brochure, however we reserve the right to change and/or adjust and/or amend specifications, equipment and availability without prior notice. This leaflet cannot be regarded as final, and as such does not constitute an offer for sale of any particular tractor, equipment or so on of specification.

www.farmer.net.pl